7-1 Specifications

Model	CRF-362	
Retail Name	Creaser and Folder	
Style of Installation	Floor Model	
Feeding Mechanism	Air Suction Feed Belt	
Sheet Size 	Max. 364 x 865 mm / 14.33" x 34.05"	
	Min. 105 x 180 mm / 4.14" x 7.09"	
	Parallel Fold:	180 to 865 mm / 7.1" to 34.0"
	Letter Fold:	276 to 650 mm / 10.9" to 25.5"
	Accordion Fold:	276 to 650 mm / 10.9" to 25.5"
	Short Fold:	420 to 431.8 mm / 16.6" to 17.0"
	Double Parallel Fold:	276 to 865 mm / 10.9" to 34.0"
	Open Gate Fold:	276 to 865 mm / 10.9" to 34.0"
	Single Flap:	347 to 865 mm / 13.7" to 34.0" However, the distance between the end of the flap and the folding line should be 69 mm / 2.7" or longer. 
	Double Flaps:	416 to 865 mm / 16.4" to 34.0" However, the distance between the end of the flap and the folding lines should be 69 mm / 2.7" or longer. Also, the distance shown below should be 255 mm / 10.0" or shorter. 
Sheet Weight Range	Normal Paper:	80 to 350 gsm (with Folding) 80 to 400 gsm (without Folding)
	Coated Paper (Gloss, Matte):	105 to 350 gsm (with Folding) 105 to 400 gsm (without Folding)
	Laminated Paper:	0.2 to 0.4 mm (with Folding) 0.2 to 0.5 mm (without Folding)
Job Memory	Up to 200 jobs	
Counter	Preset Counter, Offset Counter	
Feeder Pile Height	Max. 150 mm / 5.90"	
Creasing Mechanism	One set of positive and negative	
Number of Creasing Lines	Max. 10 Creasing Lines	

Voltage/Frequency	Single Phase 200 to 240 V, 50 / 60 Hz
Rated Current	4.5 / 6.0 A (200 V, 50 / 60 Hz) 4.3 / 5.8 A (208 V, 50 / 60 Hz) 4.2 / 5.5 A (220 V, 50 / 60 Hz) 4.2 / 5.3 A (230 V, 50 / 60 Hz)
Power Consumption (Including Pump)	780 / 1,100 W (200 V, 50 / 60 Hz) 790 / 1,100 W (208 V, 50 / 60 Hz) 810 / 1,110 W (220 V, 50 / 60 Hz) 840 / 1,120 W (230 V, 50 / 60 Hz)
Machine Dimensions	W2,742 x D701 x H1,430 mm / W108.0" x D27.6" x H56.3"
Noise Level	Lamax: 73.7 dB Laeq: 72.1 dB Lcpk: 87.6 dB
Machine Weight	345kg / 760.0 lb

The machine design and specifications are subject to change without notice.